



# Aluminium Banding Alloy 3003

**Description**

Aluminium Banding slit from aluminium alloy 3003.

**Application**

Securement of jacketing and/or insulation.

**Availability**

1/2", 3/4", 1", 1,25", 1,5", 2", 4"  
(12, 19, 25, 32, 40, 50 and 100mm).

Thickness from 0,4 up to 3 mm.

**Packing**

In coils.

**Chemical composition**

Chemical analysis	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Others Each	Others Total	Al
% by weight	0,6	0,5	0,05-0,20	1,0-1,5			0,1		0,05	0,15	remainder

IMPORTANT: Insu-W-Rapid BV warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. We make no other warranties and expressly disclaim any warranties of merchantability or fitness for a particular purpose. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. No guarantees for completeness, accuracy or results is expressed nor implied. The suitability of the product to an intended use is the sole responsibility of the user. Since material choice and application method are beyond our control, we accept no liability for direct or consequential damages.

Datasheet "Aluminium Banding Alloy 3003" – April 2012 – V1.0