Datasheet





Stainless Steel Breather Spring

Available material

Material quality : AISI302*

* Breather springs made from AISI316 spring wire are available on special order only.

Packing

120 mm (4,7") 250 pcs per carton 100 mm (4") 250 pcs per carton 50 mm (2") 500 pcs per carton


Please note that other packing units are available upon request!


Application

Expansion spring to secure insulation over piping, tanks, vessels and equipment which are subject to expansion and contraction. Suitable for band with a width of up to 19 mm (3/4").

Note

Do NOT stretch the breather spring in excess of 20% of it's original length at the time of installation. 10% stretch at installation is recommended. Furthermore, the breather spring should not be used for applications whereby the expected stretch is in excess of 40% of it's original length. Then an IWR COMPRESSION SPRING shall be used.





IMPORTANT: Insu-W-Rapid BV warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. We make no other warranties and expressly disclaim any warranties of merchantability or fitness for a particular purpose. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. No guarantees for completeness, accuracy or results is expressed nor implied. The suitability of the product to an intended use is the sole responsibility of the user. Since material choice and application method are beyond our control, we accept no liability for direct or consequential damages.

Datasheet "Stainless Steel Breather Spring" – April 2012 – V1.0

INSU-W-RAPID BV, P.O. Box 3114, 5003 DC Tilburg, The Netherlands Industrial Estate De Sonman, De Sonman 15, 5066 GJ Moergestel, The Netherlands Telephone: +31 13 595 29 20, Fax: +31 13 595 29 21, E-mail: sales@insu-w-rapid.nl, www.insu-w-rapid.nl