Datasheet





MEMBRANE XT Waterproofing Membrane

Description

MEMBRANE XT is a high performance self-adhesive waterproofing membrane. It is the ideal waterproofing/ water vapour membrane to protect all substrates from damaging effects of vapour and moisture. It is recommended for external applications, including a large variety of civil, insulation and construction situations.

MEMBRANE XT is a rubberized bitumen membrane with

a high strength polyethylene film to improve resistance to tearing and some chemicals including de-icing salts and many acids. The adhesive is protected by removable release backing.

Application

Surface must be dry and free from grease, dust or loose material. MEMBRANE XT should be pressed firmly onto surface by roller.

Availability

Roll length 20 meters, roll widths 1000 mm wide. Other roll widths available upon request.

Option: MEMBRANE XT can also be supplied with a 50 mm overlapping self-adhesive side strip on one side, protected by removable release backing, to ensure perfect continuous seams.

Packing

In carton, on pallet or in crate, stored vertically.

Physical properties

Puncture resistance	Excellent > 19,6 kgs (ASTM E 154)
Total thickness	1,5 mm (60mils)
Flame spread Index	5 (ASTM E84)
Smoke Index	55 (ASTM E84)
Color	Dark grey
Tensile strength	55 N/mm ²
Overlap Adhesion	> 65 N/10 mm/width
Elongation at break	≥ 300%
Water vapour transmission	0.015 Perms maximum (ASTM E 96)
Penetration	60-80 at 25°C / 0,1 mm to DIN 1995
Weight	1,3 kg/m ²
Application temperature	> 5°C
Service temperature	-40°C to 100°C

IMPORTANT: Insu-W-Rapid BV warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture.

We make no other warranties and expressly disclaim any warranties of merchantability or fitness for a particular purpose. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. No guarantees for completeness, accuracy or results is expressed nor implied. The suitability of the product to an intended use is the sole responsibility of the user. Since material choice and application method are beyond our control, we accept no liability for direct or consequential damages.

Datasheet "MEMBRANE XT Waterproofing Membrane" - May 2015 - V1.1

INSU-W-RAPID BV, P.O. Box 3114, 5003 DC Tilburg, The Netherlands Industrial Estate De Sonman, De Sonman 15, 5066 GJ Moergestel, The Netherlands Telephone: +31 13 595 29 20, Fax: +31 13 595 29 21, E-mail: sales@insu-w-rapid.nl, www.insu-w-rapid.nl