Datasheet





Stainless Steel Welded Wire Mesh

Description

Square or rectangular welded wire mesh made from stainless steel type 304 or type 316.

Application

Used for personnel protection and fencing on and around vessels in the insulation industry.

Applicable standards

ASTM A580M-12a Standard Specification for Stainless Steel Wire

Availability

Material can be supplied in sheets or in rolls in various lengths and widths.

Roll width is 1000 mm or 2000 mm x length. Length is determined by shipping method, which determines pallet dimensions.

Packing

Material is supplied either on rolls or in sheets.

Physical properties

Wire hardness	Soft
Wire diameter	From 1.0 to 4.0mm
Mesh size	From ½" to 4" (12.7 to 100mm)

Chemical properties

For Type 304

Chemical analysis % by weight	С	Mn	Р	S	Si	Cr	Ni	Мо	N	Cu	Other elements
Type 304	0,08	2,00	0,045	0,03	0,75	18,0-20,0	8,00-10,5		0,01		

For Type 316

Chemical analysis	С	Mn	Р	S	Si	Cr	Ni	Мо	N	Cu	Other elements
% by weight											
Type 316	0,08	2,00	0,045	0,03	0,75	16,0-18,0	10,0-14,0	2,0-3,0	0,10-0,16		

IMPORTANT: Insu-W-Rapid BV warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. We make no other warranties and expressly disclaim any warranties of merchantability or fitness for a particular purpose. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. No guarantees for completeness, accuracy or results is expressed nor implied. The suitability of the product to an intended use is the sole responsibility of the user. Since material choice and application method are beyond our control, we accept no liability for direct or consequential damages.

Datasheet "Stainless Steel Welded Wire Mesh" - April 2012 - V1.0

INSU-W-RAPID BV, P.O. Box 3114, 5003 DC Tilburg, The Netherlands Industrial Estate De Sonman, De Sonman 15, 5066 GJ Moergestel, The Netherlands Telephone: +31 13 595 29 20, Fax: +31 13 595 29 21, E-mail: sales@insu-w-rapid.nl, www.insu-w-rapid.nl