

# **TRU-FIT PRODUCTS**

### **Tru-Roc 1200 Pipe Insulation**



Tru-Roc 1200 Pipe Insulation is produced from the industry's highest quality stone wool. Our pipe covering products can be used up to 1200° F (650° C) per ASTM C447 for use on High Temperature pipes used in the power and petro-chemical systems.

Tru-Roc 1200 Pipe Insulation products are cut in half and quad sections on larger sizes and are available plain or with ASJ (All Service Jacket) or FSK (Foil Scrim Kraft). Tru-Roc 1200 Pipe Insulation is available in 3' lengths; pipe sizes .5" through 24" and thicknesses 1" through 6" in half-inch increments. Please call for sizes above 24"

Our Materials are non-wicking water repellent made from stonewool and provide corrosion resistance from the base raw materials used in our products.

#### **Insulation Specialists**

Tru-Fit Products is your insulation specialist with our team having over 300 years of cumulative experience in the industry. You can be assured you will receive a quality insulation product that will fit your insulation requirements.

700 Airport Rd. Waverly, TN 37185 (800) 759-7826 Toll Free (931) 296-1550 Direct (931) 296-5755 Fax



# TRU-FIT PRODUCTS

# **Tru-Roc 1200 Pipe Insulation**

**ASTM Performance** 

ASTM C335 BTU.in/hr. °F.ft<sup>2</sup> (W/m.K)

.221 (.0318)
.239 (.0345)
.253 (.0365)
.299 (.0432)
.350 (.0504)
.383 (.0553)
.464 (.0669)
.549 (.0792)
.660 (.0952)

ASTM C547 Material Standard – Type I & II -

1200° Grade A

ASTM C585 Dimensions – Passes

ASTM E133 Non-Combustible

ASTM C411 Hot Surface Performance - Passes 1200° F (650° C)

ASTM 356 Linear Shrinkage <0.4% at 1200° F (650° C)

ASTM E84 Surface Burning – Flame

Spread/Smoke Developed – 25/50 or

Less

ASTM C665 Corrosiveness - Passes

ASTM C795/C692/C871 Stainless Steel - Passes

ASTM C1338 Fungi Resistance – Passes

ASTM C1104 Moisture <1% Weight

Sorption

700 Airport Rd. Waverly, TN 37185 (800) 759-7826 Toll Free (931) 296-1550 Direct (931) 296-5755 Fax

Disclaimer and Limitation of Warranty: Tru-Fit Products makes no representation or claim regarding user/purchaser's use or applicability of products used. Tru-Fit Products advises user/purchaser to consult with appropriate professionals regarding intended use. Tru-Fit Products makes no warranty, expressed or implied, and disclaims all warranties including warranties of merchantability and fitness for a particular purpose.